

SEALING MATERIAL COMPOSITION FOR LIQUID CRYSTAL DISPLAY CELL

Publication number: JP2001100224

Publication date: 2001-04-13

Inventor: KITAMURA TADASHI

Applicant: MITSUI CHEMICALS INC

Classification:

- International: *G09F9/30; C08G59/50; C08K5/54; C08K5/541; C08K9/04; C08L23/00; C08L33/08; C08L83/04; C08L91/06; C09K3/10; G02F1/1339; G02F1/1341; G09F9/00; G09F9/30; C08G59/00; C08K5/00; C08K9/00; C08L23/00; C08L33/00; C08L83/00; C08L91/00; C09K3/10; G02F1/13; G09F9/00; (IPC1-7): G02F1/1339; C08G59/50; C08K5/541; C08K9/04; C08L23/00; C08L33/08; C08L83/04; C08L91/06; C09K3/10; G02F1/1341; G09F9/00*

- European:

Application number: JP19990274144 19990928

Priority number(s): JP19990274144 19990928

Report a data error here

Abstract of JP2001100224

PROBLEM TO BE SOLVED: To surely produce a liquid crystal display panel which can cope with a primary adhesion method by a sheet heat press can be applied and which maintains high sealing reliability is secured in a high temperature environment. **SOLUTION:** The sealing material for a liquid crystal display cell frame is a single-liquid sealing material having the features that a hardened film having 100 μ m thickness of the sealing material for a liquid crystal display cell shows <30 g/m² 24 hours of 60 deg.C moisture permeation which represents the amount of water vapor permeating the film in a 60 deg.C and 95% relative humidity environment for 24 hours.

Data supplied from the *esp@cenet* database - Worldwide